


CRANE TECHNOLOGY

Overhead cranes are a staple in warehouses and industrial settings around the world. Materials need to be lifted, stacked and moved constantly and reliably. To provide this, crane builders and users require dependable and repeatable performance with minimal maintenance.

VAHLE's line of conductor bar and festoon systems offer robust and economical solutions for power and control systems for any crane type. Additionally, as cranes become more advanced, VAHLE has proven high-rate data communication and millimeter precise positioning solutions.

VAHLE has conductor bar and festoon solutions for any application type and any environment - process cranes, transfer cars, work station cranes, steel mill cranes, bucket conveyors, gantry cranes and more.

The following pages provide an overview of VAHLE solutions and allow you to select the optimal product for your application.



WHAT SOLUTIONS DOES VAHLE OFFER FOR YOUR CRANE?

ELECTRIFICATION



ENCLOSED CONDUCTOR BAR

See page 6 & 7 for light to medium duty conductor bar solutions under



TRACK FESTOON SYSTEMS

See page 12 & 13 for our track festoon systems, ideal for light to medium duty applications requiring cable management.



INSULATED CONDUCTOR BAR

See page 8 & 9 for insulated conductor bar solutions from 100 - 1500 amps, ideal for light and heavy duty.



I-BEAM FESTOON CARRIERS

See page 14 & 15 for I-beam festoon carrier solutions. Multiple types exist for medium to heavy duty applications.



OPEN CONDUCTOR BAR

See page 10 & 11 for open conductor bar solutions for up to 3000 amps, ideal for the most demanding applications.

AUTOMATION POSITION

AUTOMATION



ABSOLUTE POSITIONING SYSTEMS

See page 16 & 17 for APOS, our absolute positioing system accurate down to +/- 1mm.



DATA COMMUNICATION SYSTEMS

See page 18 & 19 for our fully secure SMG-X data communication system.

WHICH SOLUTION IS RIGHT FOR YOU?

VAHLE's electrification solutions include a variety of conductor bar and festoon products to meet any demand. This includes c-track & enclosed conductor bars for lighter duty applications such as EOT cranes and process cranes. We also offer insulated unipole, uninsulated open conductor, and multiple I-Beam carriers. You can find these medium to heavy duty solutions on high load cranes in places like industrial metal processing facilities, smelting plants, and port applications.

When selecting the optimal solution for your application, consider

and environmental conditions.

MEDIUM **DUTY**

INSULATED CONDUCTOR RAILS

UP TO 1500 **AMPS**

LIGHT **DUTY**

2.0t

ENCLOSED CONDUCTOR BARS

UP TO 200 **AMPS**

TRACK
FESTOON SYSTEMS



SELECTING THE RIGHT SOLUTION, DOESN'T HAVE TO BE COMPLICATED.



KBH

PRODUCT SUMMARY

4-5 Conductors 600 Max. Voltage 200 Amps Indoor/outdoor rated

COMMON APPLICATIONS

Light duty overhead crane & electric hoists.

MKH

PRODUCT SUMMARY

6-10 Conductors 600 Max. Voltage 200 Amps Indoor/outdoor rated

COMMON APPLICATIONS

Light duty overhead crane & electric hoists.

CLASS LEADING SOLUTIONS FOR RELIABLE CRANE ELECTRIFICATION

SAVE TIME & COST ON MAINTENANCE

Current collectors and their contact brushes are wear items and require inspection and periodic replacement for optimal system operation. Standard enclosed systems require travel to either end for collector removal and inspection.



COLLECTOR REMOVAL

Exclusive VAHLE solution allows for the removal of the current collector along the length of the system. Combine the removal section with isolations to create safe zones for crane maintenance.

MULTIPLE SAFETY FEATURES TO PROTECT PERSONNEL

Conductors can be interrupted electrically to allow for the creation of zones. Utilizing these zones, you can create maintenance areas for increased safety. Combine these areas with collector removal sections for added benefit.



ISOLATIONS

Conductors can be interrupted electrically to allow for the creation of zones. Utilizing these isolations, you can create maintenance zones for increased safety and ease of maintenance.

PREVENT DAMAGING BUILD-UP

Very few warehouses and mills are spotless and free of dirt or debris and some are subjected to exposure of corrosive fumes. To combat this, VAHLE offers an exclusive dual sealing strip to prevent damage and protect your system.





SEALING STRIP

Dual neoprene sealing strips available for complete enclosure of conductor bar. Provides protection against hazards & debris such as humidity, corrosive gases, dust and dirt.



SOLUTIONS UP TO 1500 AMPS

KEY SPECS

UL Listed
IP 23 protected
Indoor & outdoor use
Curves possible
Transfers & switches possible
Isolations for sectionalizing/zoning

U25 - U35

PRODUCT SUMMARY

U25 and U35 offer exclusive VAHLE design conductors in aluminum-stainless steel and copper for efficient and cost effective energy transfer for medium to high load cranes.

COMMON APPLICATIONS

Medium to heavy duty overhead cranes and process cranes, typically found in mills, material handling and heavy metal smelters.



Copper (C) or Aluminum + Stainless Steel (AE) Conductors

INSTALLS QUICKLY

Insulated conductor bars are supplied in 19' 8" (6m) lengths, requiring fewer joint splices than most other systems.

Fewer joints means faster installation times for your team.



U20- U30

PRODUCT SUMMARY

U20 & U30 offer solid copper conductors for heavy duty and demanding applications with increased wear resistance and minimal maintenance requirements.

COMMON APPLICATIONS

Medium to heavy duty overhead cranes and process cranes, typically found in mills, material handling and heavy metal smelters.





HEAVY DUTY SOLUTIONS UP TO 3000 AMPS

IDEAL FOR

Heavy duty moving equipment in smelters, foundries, steel mills, ship yards, coking installations and cement plants.

THE **ORIGINAL**CONDUCTOR BAR

Our open conductor bars were originally developed by VAHLE in 1912. Featuring a time proven design, these conductor bars provide reliable and consistent electrification for the most demanding applications.

F45

PRODUCT SUMMARY

Steel T-Bar with copper conductor Up to 1800 amps Multiple insulator types available Hot galvanized or coated options

DEPENDABLE IN THE MOST DEMANDING CONDITIONS

Ideal for environments with extreme heat, corrosive conditions and intensive environmental hazards. Our open conductor bars can handle temperatures up to 400°F and amperage requirements over 3000.

RELIABLE PERFORMANCE

Featuring a robust design that has been perfected over 100 years of operation. Open conductors can handle the toughest jobs out there without complaint.

C45

PRODUCT SUMMARY

Solid copper construction
Up to 3000 amps
Multiple insulator types available
Ideal for the most demanding tasks



1000 0000

TRACK FESTOON SYSTEMS

LIGHT TO MEDIUM DUTY CABLE MANAGEMENT SOLUTIONS

KEY SPECS

Multiple track types Indoor & outdoor use Curves possible Flat or round festoon cables Exlusive PVC track solution Galvanzied steel sealed rollers

ECONOMIC &

DEPENDABLE

Provide power and control signals for your standard light to medium duty crane with cost effective track options.

C-TRACK

PRODUCT SUMMARY

Multiple track sizes available Heavy duty C-track (S2,S3) for larger cable packages Flat or round cable carriers Stainless steel versions available

COMMON APPLICATIONS

Light duty overhead crane & electric hoists.

DIAMOND TRACK

PRODUCT SUMMARY

Square tube track festoon system Optimized for curves Flat or round cable carriers Stainless steel versions available

COMMON APPLICATIONS

Light duty crane & electric hoists requiring multiple track

QUICK TURN AROUND

IN-STOCK SPARES

Avoid costly downtime with quick turn around on spare parts for maintenance requirements.

K1 TRACK

PRODUCT SUMMARY

Exclusive PVC construction Ideal for corrosive & hazardous site conditions. Glider style carrier available Stainless steel accessories

COMMON APPLICATIONS

Light duty overhead crane & electric hoists in hazardous or demanding site conditions.



GLIDE CARRIER SPECIALIZED FOR DEMANDING ENVIRONMENTS

VAHLE offers K1 as a specialized PVC track festoon solution for hazardous and corrosive environments.

I-BEAM CABLE CARRIERS

MEDIUM TO HEAVY DUTY APPLICATIONS

KEY SPECS

Medium duty carriers: W55, W65, W75
Heavy duty carriers: W125, W135, W145
Indoor & outdoor use including ocean climate
Travel speeds up to 1000 ft/min
Operating temperatures: -22°F to 122°F
Load capacity up to 1700lbs
Multiple saddle arrangements
Motorized options available

NO MATTER THE SYSTEM, WE'VE GOT YOUR CARRIER.



FULL RANGE OF CARRIERS FOR ANY APPLICATION



Steel, nylatron, and vulkollan wheels available.

TRAVEL SPEED UP TO 300 M/MIN

SIMPLE WHEEL REPLACEMENT

Without removing carrier from system.

MULTIPLE SADDLE OPTIONS

Galvanized steel and aluminum construction.

COMMON APPLICATIONS

Medium to heavy duty overhead cranes, stacker cranes, process cranes and STS cranes.

SAVE TIME WITH AVAILABLE PRE-ASSEMBLY

15

ABSOLUTE POSITIONING SYSTEMS

PRECISE POSITIONING FOR AUTOMATION

Accurate and reliable positioning data is critical to implementing automated processes in your facility. VAHLE's line of vPOS products offer millimeter precise positioning and are easily integrated with our electrification solutions.

Implementing automation procedures to your facility can have many positive effects including increased production, reduced cost, increased worker safety and improved quality.

INDUSTRY 4.0 SOLUTIONS

Accurate and reliable positioning data is critical to implementing automated processes in your facility.

VAHLE's line of vPOS products offer millimeter precise positioning and full integration with our electrification solutions.



PRODUCT SUMMARY

System length: Up to 260m

Travel speed: 6m/s

Temperature range: 32°F - 122°F Resistant to dirt, dust and humidity Integrates seemlessly with KBH & MKH

COMMON APPLICATIONS

Process and operation cranes requiring semi or full automation capabilities. Full retrofit capabilities for existing applications.

EASY INSTALLATION WITH EXISTING CONDUCTOR BAR

APOS contactless installs directly into the existing housing of KBH and MKH. No additional profiles or materials are required.

16

SIMPLE & RELIABLE TECHNOLOGY

VAHLE's positioning systems operate in a similar manner to conductor bar.
Utilizing the same profiles, the conductive material is replaced with a magnetic code band. In place of the traditional current collector, a readhead travels along the magnetic code band and transmits positioning data to your system.

U20 APOS MAGNETIC

PRODUCT SUMMARY

System length: Up to 515m Travel speed: 12m/s

Temperature range: 0°F - 122°F Increased misalignment tolerances

Proven APOS technology combined with robust U20

profile

COMMON APPLICATIONS

Process and operation cranes requiring semi or full automation capabilities with curves and higher operating speeds.

OPTIMIZE

YOUR POTENTIAL

VAHLE offers the required power, positioning and data communication solutions you need to reliably automate your equipment.





FULLY SECURE DATA TRANSMISSION

SMGX

PRODUCT SUMMARY

Data rate: 100 Mbit/s
System length: Up to 500m
Travel speed: Max. 130m/min
Temperature: 0°F - 122°F
Indoor and outdoor use

COMMON APPLICATIONS

Process and operation cranes requiring semi or fully automation capabilities and remote operation.

DEMANDING DATA: MORE EFFICIENCY.

LESS DOWNTIME.

SMG-X features an extruded aluminum profile with protective treatment applied to withstand the harshest environments. Available for use inside or outside, it is unaffected by wind, frost, salt or other debris.



SAFE & SECURE DATA COMMUNICATION

Traditional data communication platforms such as WIFI and leaky coax are subject to interference issues. VAHLE's vCOM solutions offer fully secure high speed communication within a specially designed wave guide. Your data signal is fully contained within the SMG-X profile, removing interference issues while increasing performance and worker safety.

COMPLETE SOLUTIONS FROM A SINGLE PROVIDER

All of VAHLE's conductor bar, positioning and data communication solutions can fully integrate to provide a complete electrification and automation package from a single source.

SMGX ANTENNA

Multi node connection.

Ready for 800 MHz frequency bandwidth.

SPECIAL ROLLER DESIGN

For guiding the antenna within the SMGX waveguide, these rollers ensure a reliable connection of data signals between the mobile consumer and stationary source.

Bearings for high velocity operation (> 300 m/min.)

High tolerances allow consistent performance in any environment.

VAHLE

PAUL VAHLE GmbH & Co. KG

Westicker Str. 52 59174 Kamen Germany

Phone: +49 2307 704-0 info@vahle.de

www.vahle.com



AVAHLE

MAHIE

VAHLE Incorporated

407 Cane Island Pkwy Katy, TX, 77494, USA

Phone: +1 713-465-9796 sales@vahleinc.com

www.vahleinc.com

connect with us!

@vahleinc







